

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property  
Organization  
International Bureau



528130

(43) International Publication Date  
1 April 2004 (01.04.2004)


PCT

(10) International Publication Number  
**WO 2004/027755 A1**

- (51) International Patent Classification: **G10L 13/06**
- (21) International Application Number: **PCT/IB2003/003554**
- (22) International Filing Date: **8 August 2003 (08.08.2003)**
- (25) Filing Language: **English**
- (26) Publication Language: **English**
- (30) Priority Data:  
**02078850.1 17 September 2002 (17.09.2002) EP**
- (71) Applicant (for all designated States except US): **KONINKLIJKE PHILIPS ELECTRONICS N.V. [NL/NL]; Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).**
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): **GIGI, Ercan, F. [NL/NL]; c/o Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).**
- (74) Agent: **DUIJVESTIJN, Adrianus, J.; Philips Intellectual Property & Standards, Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).**
- (81) Designated States (national): **AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.**
- (84) Designated States (regional): **ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).**

[Continued on next page]

(54) Title: **METHOD OF SYNTHESIZING CREAKY VOICE**



(57) Abstract: The invention relates to a method of synthesizing a signal comprising the steps of: a) providing of a first signal having first periods of a first type and second periods of a second type in an alternating sequence, b) selecting of one of the pitch bells for a first one of the required pitch bell locations by identifying the nearest neighboring period of the first one of the required pitch bell locations being of the first type, and selecting of the pitch bell of the identified period, c) selecting of one of the pitch bells for a second one of the required pitch bell locations by identifying a nearest neighboring period of the second one of the required pitch bell locations having the second type, and selecting the pitch bell of the identified period, whereby the steps b) and c) are carried out for all of the required pitch bell locations.

WO 2004/027755 A1